

PRODUCT INFORMATION



A Product of Valvoline Cummins Ltd.

Valvo Freez 32 / 46 / 68

PRODUCT DESCRIPTION

Valvo Freez 32 / 46 /68 are blended from specially selected lube base stocks to provide low pour point, good chemical stability & ready solubility in liquefied refrigerants.

These oils are straight mineral type having inherent resistance to oxidation and deposit formation.

APPLICATIONS

Valvo Freez 32/46/68 are recommended for lubricant in wide range of compressors. The product can be used in conventional refrigerants, except sulphur dioxide, in both reciprocating & rotary compressors.

The products are also suitable in properly designed and maintained refrigeration systems when evaporator temperatures are lower than the pour point of the oil.

PERFORMANCE BENEFITS

- High fluidity at low temperature.
- Reduce deposit formation thus keeping compressor parts clean.
- Ensure high condenser efficiency.
- Longer service life due to good oxidation & thermal stability.

TYPICAL CHARACTERSTICS

ISO VG	32	46	68
Kinematic Viscosity, cSt @ 40°C	32	46	68
Flash Point, COC, °C, min.	190	208	214
Pour Point, °C, max.	-45	-42	-36

Available Packs: 20, 210 Ltrs.

9/2008



Valvoline Cummins Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins Diesel Sales and Service (India) Ltd.
52, Okhla Industrial Estate, Phase III, New Delhi – 110 020
Phone: (011) 41613444 – 48, Fax: (011) 41613453
Visit us at: www.valvolinecummins.com

