

PRODUCT INFORMATION



A Product of Valvoline Cummins Ltd.

Valvoline Gear Gard EP 90/140

PRODUCT DESCRIPTION

Valvoline Gear Gard EP 90 & 140 are multipurpose sulphur-phosphorus based extreme pressure superior quality heavy-duty gear oils. The products have been specially formulated to meet severe duty operation in heavily loaded gear systems, such as hypoid, spiral, bevel, worm gears, where an active GL-4 performance oils are required.

The products offer excellent performance under severe stress, heavy loads and low temperatures.

Valvoline Gear Gard EP 90/140 have been fully inhibited with advanced additive chemistry to combat extreme pressure, wear, corrosion, oxidation and foaming.

APPLICATIONS

Valvoline Gear Gard EP 90/140 are recommended for hypoid, spiral, bevel or worm gear transmission system of cars, buses, trucks and tractors requiring EP type lubricants.

PERFORMANCE STANDARDS

API GL-4
MIL-L-2105
IS 1118 : 1992

TYPICAL CHARACTERISTICS

SAE Grade	90	140
Appearance	Clear & Bright	Clear & Bright
Kinematic Viscosity, @ 100°C cSt	16.8	27.5
Viscosity Index	96	94
Flash Point, COC, °C, Min.	210	220
Pour Point, °C, max	-9	-9

Available Packs: (SAE 90) 0.5, 1, 5, 20, 50 & 210 Ltrs.

Available Packs: (SAE 140) 0.5, 1, 5, 20 & 210 Ltrs.

9/2008



Valvoline Cummins Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins Diesel Sales and Service (India) Ltd.
52, Okhla Industrial Estate, Phase III, New Delhi – 110 020
Phone: (011) 41613444 – 48, Fax: (011) 41613453
Visit us at: www.valvolinecummins.com

