

PRODUCT INFORMATION



A Product of Valvoline Cummins Ltd.

Valvoline Superkool Xtra

PRODUCT DESCRIPTION

Valvoline Superkool Xtra is formulated with highly pure monoethylene glycol and selected rust and corrosion inhibitor to protect the metal parts against corrosion and prevents foaming and scale formation. It helps maintain engine interior sparkling clean and enhances heat transfer process which ensures peak engine cooling and longer life.

Valvoline Superkool Xtra is compatible with any type of water even upto a hardness of 700 ppm.

RECOMMENDED DOSAGE

Recommended dilution ratio (coolant: water):

- For Heavy Duty Applications: 1:4
- For Light Duty Applications: 1:7

DIRECTIONS FOR USE

1. Drain and flush cooling system with water.
2. Check system for leakages, if any.
3. Top up periodically with Valvoline Superkool Xtra upto maximum mark on the expansion bottle.

PERFORMANCE BENEFITS

- Protection against corrosion to cooling system metals.
- Prevents hot weather boil-overs and cold weather freeze-ups.
- Does not harm non-metallic components like gaskets, hoses etc.
- Environmental friendly.

APPLICATION

Recommended for use in radiators of all commercial vehicles, tractors, passenger cars, jeeps, MUVs and SUVs.

TYPICAL CHARACTERISTICS

Color	Green
Density @ 20°C, kg/l	1.058
Ph	7.8
Reserve Alkalinity	3.5
Boiling Point, °C	102

Available Packs: 0.5, 1, 3 & 210 Ltrs.

9/2008



Valvoline Cummins Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins Diesel Sales and Service (India) Ltd.
52, Okhla Industrial Estate, Phase III, New Delhi – 110 020
Phone: (011) 41613444 – 48, Fax: (011) 41613453
Visit us at: www.valvolinecummins.com

