

PRODUCT INFORMATION



A Product of Valvoline Cummins Ltd.

Valvoline Transfluid III

PRODUCT DESCRIPTION

Valvoline Transfluid III is formulated with a blend of high tech basestocks combined with advanced additive technology to meet the challenging demands of an automatic transmission environment. Valvoline Transfluid III is designed to provide better heat resistance, cold flow capabilities and transmission shutter resistance than conventional automatic transmission fluids.

Valvoline Transfluid III Advantages:

- **Low Temperature Protection:** Flows easily at low temperatures.
- **Friction Modified:** Contains additives to protect automatic transmission hardware.
- **Cleaner Transmission:** Minimizes sludge and varnish deposits.
- **Compatibility:** Protects transmission seal materials.
- **Anti-Shudder:** Provides superior anti-shudder performance.

PERFORMANCE STANDARDS

Valvoline Transfluid III meets the requirements of:

- DEXRON®-III(H)
- MERCON®
- Allison C-4
- Caterpillar TO-2

APPLICATIONS

It is recommended for use in automatic transmission for GM & Ford passenger cars and light duty truck transmissions.

This product is also suitable for use in powershift transmissions, torque converters(H)hydrostatic transmissions and applications such as in air compressors(H)hydraulic pumps and other types of service where an ATF is recommended.

TYPICAL CHARACTERISTICS

Kinematic Viscosity, cSt @ 40°C	38
Kinematic Viscosity, cSt @ 100°C	7.5
Viscosity Index, min.	195
Brookfield Viscosity, cP @ -40°C, max.	20,000
Flash Point, °C (PMCC), min.	170

Available Packs: 210 Liters

9/2008



Valvoline Cummins Ltd.
A Joint Venture Company of
Valvoline International Inc., USA
& Cummins Diesel Sales and Service (India) Ltd.
52, Okhla Industrial Estate, Phase III, New Delhi – 110 020
Phone: (011) 41613444 – 48, Fax: (011) 41613453
Visit us at: www.valvolinecummins.com

