

---

# PRODUCT INFORMATION



A Product of Valvoline Cummins Pvt. Ltd.

---

## Valvoline GEO 15W-40 S

### PRODUCT DESCRIPTION

Valvoline GEO 15W-40S has been specially developed for stationery engine running on natural gas. The product provides exceptional control of deposits, wear, oil oxidation & oil nitration in both naturally aspirated and turbo charged natural gas engines. The use of Valvoline GEO 15W-40S, which is based on a specially selected additive system, ensures reduction in carbon and ash deposit during service.

### APPLICATIONS

Valvoline GEO 15W-40S is recommended for use in engines manufactured by Cummins India Ltd., Waukesha, Dresser Rand, Caterpillar, Detroit Diesel operating on CNG.

### PERFORMANCE STANDARDS

API CF

### PERFORMANCE BENEFITS

- Excellent deposit and wear control.
- Good scuff protection.
- Excellent oxidation / nitration control.
- Low ash

---

### TYPICAL CHARACTERISTICS

Kinematic Viscosity, cSt @ 40°C	114.50
Kinematic Viscosity, cSt @ 100°C	14.80
Viscosity Index	135
Flash Point, COC, °C	220
TBN, mg KOH/g	5.00
Sulphated Ash, % wt	0.45

---

**Available Packs:** Consult your Valvoline Representative.

4/2017



Valvoline Cummins Pvt. Ltd.  
A Joint Venture Company of  
Valvoline International Inc., USA  
& Cummins India Ltd.  
3<sup>rd</sup> Floor, Vipul Plaza, Suncity, Sector-54, Gurgaon-122003  
Phone: (0124) 4721200 / 4721300, Fax: (0124) 4721299  
Visit us at: [www.valvolinecummins.com](http://www.valvolinecummins.com)

